



NOTES :

- CLUTCH, PENDANT BOLT AND HEADER HANGER SUPPORT DRILLINGS LOCATED FROM DAYLITE, REGARDLESS OF DOOR LAP SIZE. G.A.L. PREFERRED 1 1/4" LAP AT THE LEADING EDGE ONLY.
- DRAWINGS ARE BASED ON EQUAL CAR AND HOISTWAY DOOR HEIGHTS ± 1 INCH. IF DOOR HEIGHTS DIFFER NOTIFY G.A.L. AND HOISTWAY DOOR MFG'R.

- WARNING -
G.A.L. PROPRIETARY INFORMATION
REPRODUCTION AND/OR USE OF ALL OR ANY PART OF THIS (THESE) PAGE(S) OR DRAWING(S) OR THE INFORMATION HEREIN, WITHOUT THE EXPRESS PERMISSION OF G.A.L. MANUFACTURING CORPORATION IS STRICTLY PROHIBITED BY LAW.
- VIOLATORS WILL BE PROSECUTED -

46-47-48	94	9	2	38	23
43-44-45	88	8	4	35	(45) 23 (43-44) 19
40-41-42	82	7	6	32	19
37-38-39	76	7	3	29	15
34-35-36	70	6	5	26	15
31-32-33	64	6	2	23	15
28-29-30	58	5	4	20	(20) 16 (28-29) 11
25-26-27	52	4	6	17	11
22-23-24	46	4	3	14	11
DOOR OPNG.	A	B	C	D	M

DIMENSION TABLE

AS SHOWN L.H. _____
SYMMETRICALLY _____
OPPOSITE R.H. _____
DOOR HEIGHT _____
JAMB HEIGHT _____

* REQUIRED ONLY IF ELECTRIC EYES BY G.A.L.
(36 x 84 D.O. SHOWN)

G.A.L. MANUFACTURING CORP.
50 E. 153rd STREET BRONX, N.Y. 10451

CAR REINFORCEMENT AND DRILLINGS SINGLE SPEED
TYPE "A" HANGER W/REAL SAFETY EDGE AND ELECTRIC EYES OR SCANGUARD 22-48 D.O.

SCALE	3/32	DATE	10-31-94
DWG. BY			
REV. No.			8231