



DIMENSION TABLE					
DOOR OPENING	A	B	C	D	M
46-47-48	94	9	2	38	23
43-44-45	88	8	4	35	(45) 23 (43-44) 19
40-41-42	82	7	6	32	19
37-38-39	76	7	3	29	15
34-35-36	70	6	5	26	15
31-32-33	64	6	2	23	15
28-29-30	58	5	4	20	(30) 15 (28-29) 11
25-26-27	52	4	6	17	11
22-23-24	46	4	3	14	11

36 x 84 DOOR OPENING SHOWN

NOTES:

- CLUTCH, PENDANT BOLT AND HEADER HANGER SUPPORT DRILLINGS LOCATED FROM DAYLITE, REGARDLESS OF DOOR LAP SIZE. G.A.L. PREFERS $1\frac{1}{4}$ LAP AT THE LEADING EDGE ONLY.
- DRAWINGS ARE BASED ON EQUAL CAR AND HOISTWAY DOOR HEIGHTS ± 1 INCH. IF DOOR HEIGHTS DIFFER, NOTIFY G.A.L. AND HOISTWAY DOOR MANUFACTURER.

AS SHOWN L.H. _____

SYMMETRICALLY OPPOSITE R.H. _____

DOOR HEIGHT _____

JAMB HEIGHT _____

- WARNING -
G.A.L. PROPRIETARY INFORMATION
REPRODUCTION AND/OR USE OF ALL OR ANY PART OF THIS (THESE) PAGE(S) OR DRAWING(S) OR THE INFORMATION HEREIN, WITHOUT THE EXPRESS PERMISSION OF G.A.L. MANUFACTURING CORPORATION IS STRICTLY PROHIBITED BY LAW.
- VIOLATORS WILL BE PROSECUTED -

A	TEMPLATE UPDATE	11-01-13
REV	DESCRIPTION	DATE

CAR REINFORCEMENT AND DRILLINGS SINGLE SPEED
POWER OPERATED CAR DOOR WITH DOOR LINK AND BRACKET -
MANUAL HATCH DOORS INSTALLATION



G.A.L. MANUFACTURING CORP.
50 E. 153rd STREET, BRONX, N.Y. 10451
PHONE: (718) 292-9000, FAX: (718) 292-2034
www.GAL.com, info@GAL.com

DATE 12-18-96
DOCUMENT No. 8231-6

REV A