



DOOR OVERALL HEIGHT INCLUDING GUIDE SHOE BRACKET AND 1/4\"/>

2 HATCH SILL

7/8 DIA. HOLE ON TOP OF HANGER HOUSING FOR INTERLOCK WIRE CONDUIT (IF REQUIRED)

VIEW "A"

36 x 84 DOOR OPENING SHOWN

AS SHOWN R.H. _____

SYMMETRICALLY OPPOSITE L.H. _____

DOOR HEIGHT _____

JAMB HEIGHT _____

DIMENSION TABLE					
DOOR OPENING	A	B	C	D	E
46-47-48	94	24 (FIG. 3)	12	34	22
43-44-45	88	24 (FIG. 2)	24	31	(45) 22 (43-44) 18
40-41-42	82	24 (FIG. 2)	24	28	18
37-38-39	76	24 (FIG. 2)	12	25	14
34-35-36	70	24 (FIG. 2)	12	22	14
31-32-33	64	24 (FIG. 1)	-	19	14
28-29-30	58	24 (FIG. 1)	-	16	(30) 14 (28-29) 10
25-26-27	52	18 (FIG. 1)	-	13	10
22-23-24	46	18 (FIG. 1)	-	10	10

DIMENSION TABLE			
DOOR OPENING	F	G	H
45-48	3	36 3/4	50 1/2
41-44	3	33 1/4	46 1/2
36-40	3	29 3/4	47 1/2
28-35	3	27 1/4	42
27	2	24 1/2	36
26	3	23 1/2	36
25	4	22 1/2	36
24	5	21 1/2	36
23	6	20 1/2	36
22	7	19 1/2	36

NOTES:

- INTERLOCK ROLLER RELEASE, PENDANT BOLT, EMERGENCY KEY HOLE AND HANGER DRILLINGS LOCATED FROM DAYLITE, REGARDLESS OF DOOR LAP SIZE. G.A.L. PREFERRED 3/4\"/>
- DRAWINGS ARE BASED ON EQUAL CAR AND HOISTWAY DOOR HEIGHTS ±1 INCH. IF DOOR HEIGHTS DIFFER, NOTIFY G.A.L. AND HOISTWAY DOOR MANUFACTURER.

- WARNING -
G.A.L. PROPRIETARY INFORMATION

REPRODUCTION AND/OR USE OF ALL OR ANY PART OF THIS (THESE) PAGE(S) OR DRAWING(S) OR THE INFORMATION HEREIN, WITHOUT THE EXPRESS PERMISSION OF G.A.L. MANUFACTURING CORPORATION IS STRICTLY PROHIBITED BY LAW.

- VIOLATORS WILL BE PROSECUTED -

REV	DESCRIPTION	DATE
B	LAYOUT UPDATE	11-18-13
A	LAYOUT UPDATE	7-11-13

HATCH REINFORCEMENT AND DRILLINGS SINGLE SPEED TYPE "A" HANGER WITH REEL OR SPRING DOOR CLOSER 22-48 DOOR OPENING



G.A.L. MANUFACTURING CORP.

50 E. 153rd STREET, BRONX, N.Y. 10451

PHONE: (718) 292-9000, FAX: (718) 292-2034
www.GAL.com, info@GAL.com

DATE 11-11-94

DOCUMENT No.

8241

REV

B