

Car and Hatch Doors Pricing



SINGLE SPEED / POWER OPERATED
22" TO 48" x 84" OPENINGS

A VANTAGE Company

Master Door Operator: Drive arm, microswitch and equipped for nudging (add gate switch)

| Quantity | Type | Description | Opening Size | List |
|----------|----------|--|--------------|---------|
| 1 | MODL | Standard duty | 22" to 42" | 2538.12 |
| 1 | MODCTL | Standard duty - car top control | 22" to 42" | 3546.06 |
| 1 | MOVFR II | VVVF - Heavy duty - encoderless closed loop | 22" to 48" | 2771.12 |
| 1 | G | Gate switch assembly - mandatory item | 22" to 48" | 101.74 |
| 1 | G | Shielded gate switch assembly - mandatory item for North Carolina jobs | 22" to 48" | 135.64 |

Car Door Equipment

| Quantity | Type | Description | Opening Size | List |
|----------|-------|---|--------------|--------|
| 1 | S/S | Car door hanger w/ 3 1/4" rollers, track and header | 22" to 36" | 216.32 |
| 1 | S/S | Car door hanger w/ 3 1/4" rollers, track and header | 37" to 44" | 289.98 |
| 1 | S/S | Car door hanger w/ 3 1/4" rollers, track and header | 45" to 48" | 363.66 |
| 1 | LWZ-2 | Car door clutch w/ zone lock ^A | n/a | 791.10 |

Hatch Door Equipment

| Quantity | Type | Description | Opening Size | List |
|----------|------|--|--------------|--------|
| 1 | S/S | Hatch door hanger w/ 3 1/4" rollers, top safety retainers ^B and track | 22" to 36" | 112.26 |
| 1 | S/S | Hatch door hanger w/ 3 1/4" rollers, top safety retainers ^B and track | 37" to 44" | 149.68 |
| 1 | S/S | Hatch door hanger w/ 3 1/4" rollers, top safety retainers ^B and track | 45" to 48" | 185.92 |
| 1 | S/S | Spring door closer | n/a | 88.88 |
| 1 | MOH | Interlock - switch, keeper, roller release, linkage and hardware | n/a | 168.38 |

Optional Door Equipment

| Quantity | Type | Description | List |
|----------|----------|---|--------|
| 1 | DPFS | Formula Systems standard power supply - traditional operators | 648.94 |
| 1 | DPFS | Formula Systems integrated power supply - MOVFR operators only | 570.62 |
| 1 | DPTT | Tri-Tronics standard power supply - traditional operators | 982.18 |
| 1 | DPTT | Tri-Tronics integrated power supply - MOVFR operators only | 906.18 |
| 1 | DPSG | Scanguard standard power supply - traditional operators | 596.32 |
| 1 | DPSG | Scanguard integrated power supply - MOVFR operators only | 521.50 |
| 1 | | Flush type key box - #4 satin stainless steel cover | 74.60 |
| 1 | KMO | Key | 42.80 |
| 1 | Handheld | Handheld parameter w/ 7' cable - for use with MOVFR II operators only | 251.40 |

Issue date: 01/01/21

**NORMAL DISCOUNT TO QUALIFIED ELEVATOR CONTRACTORS - PRICES SUBJECT TO CHANGE WITHOUT NOTICE
PRICES BASED ON G.A.L. STANDARD CLEARANCE AND SPACE REQUIREMENTS - F.O.B. BRONX, NEW YORK**

CODE REQUIREMENTS:

(A) Zone lock complies with ASME A17.1 RULE 111.12, CAN/CSA-B44-94 RULE 3.6.5.6

(B) Top safety retainers comply with ASME A17.1 RULE 110.11h, CAN/CSA-B44-94 RULE 2.11.10.5

Car and Hatch Doors Pricing



TWO SPEED / POWER OPERATED
22" TO 72" x 84" OPENINGS

A VANTAGE Company

Master Door Operator: Drive arm, microswitch and equipped for nudging (add gate switch)

| Quantity | Type | Description | Opening Size | List |
|----------|----------|--|--------------|---------|
| 1 | MODL | Standard duty | 24" to 59" | 2538.12 |
| 1 | MODCTL | Standard duty - car top control | 24" to 59" | 3546.06 |
| 1 | MOVFR II | VVVF - Heavy duty - encoderless closed loop | 24" to 72" | 2771.12 |
| 1 | G | Gate switch assembly - mandatory item | 24" to 72" | 101.74 |
| 1 | G | Shielded gate switch assembly - mandatory item for North Carolina jobs | 24" to 72" | 135.64 |

Car Door Equipment

| Quantity | Type | Description | Opening Size | List |
|----------|-------|--|--------------|--------|
| 1 | 2/SP | Car door hanger w/ 3 1/4" rollers, track (ungeared) and header | 24" to 29" | 548.40 |
| 1 | 2/SP | Car door hanger w/ 3 1/4" rollers, as above | 30" to 48" | 440.82 |
| 1 | 2/SP | Car door hanger w/ 3 1/4" rollers, as above | 49" to 60" | 548.40 |
| 1 | 2/SP | Car door hanger w/ 3 1/4" rollers, as above | 61" to 68" | 695.72 |
| 1 | 2/SP | Car door hanger w/ 3 1/4" rollers, as above | 69" to 72" | 836.02 |
| 1 | LWZ-2 | Car door clutch w/ zone lock ^A | n/a | 719.10 |

Hatch Door Equipment

| Quantity | Type | Description | Opening Size | List |
|----------|------|---|----------------------------|--------|
| 1 | 2/SP | Hatch door hanger w/ 3 1/4" rollers, top safety retainers ^B , track (ungeared), and mechanical interconnecting device ^C | 24" to 29" | 337.92 |
| 1 | 2/SP | Hatch door hanger w/ 3 1/4" rollers, as above | 30" to 46" | 264.26 |
| 1 | 2/SP | Hatch door hanger w/ 3 1/4" rollers, as above | 47" to 60" | 337.92 |
| 1 | 2/SP | Hatch door hanger w/ 3 1/4" rollers, as above | 61" to 68" | 411.60 |
| 1 | 2/SP | Hatch door hanger w/ 3 1/4" rollers, as above | 69" to 72" | 485.24 |
| 1 | 2/SP | Spring door closer | 24" to 48" | 129.80 |
| 1 | 2/SP | Spring door closer | 49" to 66" w/ dual springs | 213.98 |
| 1 | 2/SP | Spring door closer | 67" to 72" w/ dual springs | 299.34 |
| 1 | MOH | Interlock - switch, keeper, roller release, linkage and hardware | 24" to 52" | 168.38 |
| 1 | MOH | Interlock - switch, keeper, roller release, linkage and hardware | 53" to 72" | 185.92 |

Optional Door Equipment

| Quantity | Type | Description | List |
|----------|----------|---|--------|
| 1 | DPFS | Formula Systems standard power supply - traditional operators | 648.94 |
| 1 | DPFS | Formula Systems integrated power supply - MOVFR operators only | 570.62 |
| 1 | DPTT | Tri-Tronics standard power supply - traditional operators | 982.18 |
| 1 | DPTT | Tri-Tronics integrated power supply - MOVFR operators only | 906.18 |
| 1 | DPSG | Scanguard standard power supply - traditional operators | 596.32 |
| 1 | DPSG | Scanguard integrated power supply - MOVFR operators only | 521.50 |
| 1 | | Flush type key box - #4 satin stainless steel cover | 74.60 |
| 1 | KMO | Key | 42.80 |
| 1 | Handheld | Handheld parameter w/ 7' cable - for use with MOVFR II operators only | 251.40 |

Issue date: 01/01/21

**NORMAL DISCOUNT TO QUALIFIED ELEVATOR CONTRACTORS - PRICES SUBJECT TO CHANGE WITHOUT NOTICE
PRICES BASED ON G.A.L. STANDARD CLEARANCE AND SPACE REQUIREMENTS - F.O.B. BRONX, NEW YORK**

CODE REQUIREMENTS:

(A) ZONE LOCK COMPLIES WITH ASME A17.1 RULE 111.12, CAN/CSA-B44-94 RULE 3.6.5.6

(B) TOP SAFETY RETAINERS COMPLY WITH ASME A17.1 RULE 110.11h, CAN/CSA-B44-94 RULE 2.11.10.5

(C) MECHANICAL INTERCONNECTING DEVICE COMPLIES WITH ASME A17.1 RULE 110.11g, CAN/CSA-B44-94 RULE 2.12.2.1.7

Car and Hatch Doors Pricing



THREE SPEED / POWER OPERATED

30" TO 72" x 84" OPENINGS (MIN. DOOR PANEL 12 1/2" WIDE)

A VANTAGE Company

Master Door Operator: Drive arm, microswitch and equipped for nudging (add gate switch)

| Quantity | Type | Description | Opening Size | List |
|----------|----------|--|--------------|---------|
| 1 | MODL | Standard duty | 30" to 59" | 2650.66 |
| 1 | MODCTL | Standard duty - car top control | 30" to 59" | 5483.04 |
| 1 | MOVFR II | VVVF - Heavy duty - encoderless closed loop | 30" to 72" | 2841.28 |
| 1 | G | Gate switch assembly - mandatory item | 30" to 72" | 101.74 |
| 1 | G | Shielded gate switch assembly - mandatory item for North Carolina jobs | 30" to 72" | 135.64 |

Car Door Equipment

| Quantity | Type | Description | Opening Size | List |
|----------|-------|--|--------------|---------|
| 1 | 3/SP | Car door hanger w/ 3 1/4" rollers, track, and header, cable geared intermediate to slow door | 30" to 52" | 860.08 |
| 1 | 3/SP | Car door hanger w/ 3 1/4" rollers, as above | 53" to 64" | 1068.08 |
| 1 | 3/SP | Car door hanger w/ 3 1/4" rollers, as above | 65" to 69" | 1281.68 |
| 1 | 3/SP | Car door hanger w/ 3 1/4" rollers, as above, but ungeared | 70" to 72" | 1450.32 |
| 1 | LWZ-2 | Car door clutch w/ zone lock ^A | n/a | 719.10 |

Hatch Door Equipment

| Quantity | Type | Description | Opening Size | List |
|----------|------|--|--------------|---------|
| 1 | 3/SP | Hatch door hanger w/ 3 1/4" rollers, top safety retainers ^B , track (ungeared), (2) mechanical (ungeared) and (2) mechanical interconnecting devices ^C | 30" to 51" | 530.84 |
| 1 | 3/SP | Hatch door hanger w/ 3 1/4" rollers, as above | 52" to 64" | 754.18 |
| 1 | 3/SP | Hatch door hanger w/ 3 1/4" rollers, as above | 65" to 69" | 976.34 |
| 1 | 3/SP | Hatch door hanger w/ 3 1/4" rollers, as above | 70" to 72" | 1204.34 |
| 1 | 3/SP | Spring door closer - shoe type | 30" to 69" | 806.80 |
| 1 | 3/SP | Spring door closer - shoe type | 70" to 72" | 993.88 |
| 1 | MOH | Interlock - switch, keeper, roller release, linkage and hardware | 55" to 72" | 185.92 |
| 1 | MOH | Interlock - switch, keeper, roller release, linkage and hardware | 55" to 72" | 185.92 |

Optional Door Equipment

| Quantity | Type | Description | List |
|----------|----------|---|--------|
| 1 | DPFS | Formula Systems standard power supply - traditional operators | 640.94 |
| 1 | DPFS | Formula Systems integrated power supply - MOVFR operators only | 570.62 |
| 1 | DPTT | Tri-Tronics standard power supply - traditional operators | 982.18 |
| 1 | DPTT | Tri-Tronics integrated power supply - MOVFR operators only | 906.18 |
| 1 | DPSG | Scanguard standard power supply - traditional operators | 596.32 |
| 1 | DPSG | Scanguard integrated power supply - MOVFR operators only | 521.50 |
| 1 | | Flush type key box - #4 satin stainless steel cover | 74.60 |
| 1 | KMO | Key | 42.80 |
| 1 | Handheld | Handheld parameter w/ 7' cable - for use with MOVFR II operators only | 251.40 |

Issue date: 01/01/21

**NORMAL DISCOUNT TO QUALIFIED ELEVATOR CONTRACTORS - PRICES SUBJECT TO CHANGE WITHOUT NOTICE
PRICES BASED ON G.A.L. STANDARD CLEARANCE AND SPACE REQUIREMENTS - F.O.B. BRONX, NEW YORK**

CODE REQUIREMENTS:

(A) ZONE LOCK COMPLIES WITH ASME A17.1 RULE 111.12, CAN/CSA-B44-94 RULE 3.6.5.6

(B) TOP SAFETY RETAINERS COMPLY WITH ASME A17.1 RULE 110.11h, CAN/CSA-B44-94 RULE 2.11.10.5

(C) MECHANICAL INTERCONNECTING DEVICE COMPLIES WITH ASME A17.1 RULE 110.11g, CAN/CSA-B44-94 RULE 2.12.2.1.7

Car and Hatch Doors Pricing



SINGLE SPEED / CENTER PARTING / POWER OPERATED
30" TO 83" x 84" OPENINGS

A VANTAGE Company

Master Door Operator: Drive arm, microswitch and equipped for nudging (add gate switch)

| Quantity | Type | Description | Opening Size | List |
|----------|----------|--|--------------|---------|
| 1 | MODL | Standard duty | 30" to 59" | 2763.20 |
| 1 | MODCTL | Standard duty - car top control | 30" to 59" | 5145.40 |
| 1 | MOVFR II | VVVF - Heavy duty - encoderless closed loop | 30" to 83" | 2923.14 |
| 1 | G | Gate switch assembly - mandatory item | 30" to 83" | 101.74 |
| 1 | G | Shielded gate switch assembly - mandatory item for North Carolina jobs | 30" to 83" | 135.64 |

Car Door Equipment

| Quantity | Type | Description | Opening Size | List |
|----------|-------|---|--------------|---------|
| 1 | C/P | Car door hanger w/ 3 1/4" rollers, track (ungeared), and header | 30" to 35" | 401.88 |
| 1 | C/P | Car door hanger w/ 3 1/4" rollers, as above | 36" to 44" | 474.72 |
| 1 | C/P | Car door hanger w/ 3 1/4" rollers, as above | 45" to 50" | 548.40 |
| 1 | C/P | Car door hanger w/ 3 1/4" rollers, as above | 51" to 59" | 613.88 |
| 1 | C/P | Car door hanger w/ 3 1/4" rollers, as above | 60" to 68" | 871.10 |
| 1 | C/P | Car door hanger w/ 3 1/4" rollers, as above | 69" to 83" | 1017.24 |
| 1 | LWZ-2 | Car door clutch w/ zone lock ^A | 30" to 83" | 719.10 |
| 1 | LW2 | Additional car door clutch | 60" to 83" | 571.78 |

Hatch Door Equipment

| Quantity | Type | Description | Opening Size | List |
|----------|-------|--|--------------|--------|
| 1 | C/P | Hatch door hanger w/ 3 1/4" rollers, top safety retainers ^B , cable geared and track ^C | 30" to 35" | 259.58 |
| 1 | C/P | Hatch door hanger w/ 3 1/4" rollers, as above | 36" to 44" | 297.00 |
| 1 | C/P | Hatch door hanger w/ 3 1/4" rollers, as above | 45" to 50" | 333.24 |
| 1 | C/P | Hatch door hanger w/ 3 1/4" rollers, as above | 51" to 59" | 370.60 |
| 1 | C/P | Hatch door hanger w/ 3 1/4" rollers, as above but ungeared with bumpers | 60" to 68" | 444.34 |
| 1 | C/P | Hatch door hanger w/ 3 1/4" rollers, as above but ungeared with bumpers | 69" to 83" | 571.98 |
| 1 | C/P | Spring door closer | 30" to 59" | 88.88 |
| 2 | C/P | Spring door closer (\$82.08 each) | 60" to 83" | 177.76 |
| 1 | MOCPH | Interlock - switch, keeper, roller release, linkage and hardware | 30" to 59" | 251.40 |
| 2 | MOH | Interlock - switch, keeper, roller release, linkage and hardware (\$155.52 each) | 60" to 79" | 336.76 |
| 2 | MOH | Interlock - switch, keeper, roller release, linkage and hardware (\$171.72 each) | 80" to 83" | 371.84 |

Optional Door Equipment

| Quantity | Type | Description | List |
|----------|----------|---|--------|
| 1 | DPFS | Formula Systems standard power supply - traditional operators | 648.62 |
| 1 | DPFS | Formula Systems integrated power supply - MOVFR operators only | 570.62 |
| 1 | DPTT | Tri-Tronics standard power supply - traditional operators | 982.18 |
| 1 | DPTT | Tri-Tronics integrated power supply - MOVFR operators only | 906.18 |
| 1 | DPSG | Scanguard standard power supply - traditional operators | 596.32 |
| 1 | DPSG | Scanguard integrated power supply - MOVFR operators only | 521.50 |
| 1 | | Flush type key box - #4 satin stainless steel cover | 74.60 |
| 1 | KMO | Key | 42.80 |
| 1 | Handheld | Handheld parameter w/ 7' cable - for use with MOVFR II operators only | 251.40 |

Issue date: 01/01/21

**NORMAL DISCOUNT TO QUALIFIED ELEVATOR CONTRACTORS - PRICES SUBJECT TO CHANGE WITHOUT NOTICE
PRICES BASED ON G.A.L. STANDARD CLEARANCE AND SPACE REQUIREMENTS - F.O.B. BRONX, NEW YORK**

CODE REQUIREMENTS:

- (A) ZONE LOCK COMPLIES WITH ASME A17.1 RULE 111.12, CAN/CSA-B44-94 RULE 3.6.5.6
- (B) TOP SAFETY RETAINERS COMPLY WITH ASME A17.1 RULE 110.11h, CAN/CSA-B44-94 RULE 2.11.10.5
- (C) SPLIT CAR & HATCH DOOR TRACKS FURNISHED WITH DOOR OPENINGS 60" TO 83"

Car and Hatch Doors Pricing



TWO SPEED / CENTER PARTING / POWER OPERATED
33" TO 83" x 84" OPENINGS (MIN. DOOR PANEL 12 1/2" WIDE)

A **VANTAGE** Company

Master Door Operator: Drive arm, microswitch and equipped for nudging (add gate switch)

| Quantity | Type | Description | Opening Size | List |
|----------|----------|--|--------------|---------|
| 1 | MODL | Standard duty | 33" to 59" | 2763.20 |
| 1 | MODCTL | Standard duty - car top control | 33" to 59" | 5145.40 |
| 1 | MOVFR II | VVVF - Heavy duty - encoderless closed loop | 33" to 83" | 2923.14 |
| 1 | G | Gate switch assembly - mandatory item | 33" to 83" | 101.74 |
| 1 | G | Shielded gate switch assembly - mandatory item for North Carolina jobs | 33" to 83" | 135.64 |

Car Door Equipment

| Quantity | Type | Description | Opening Size | List |
|----------|--------|--|--------------|---------|
| 1 | 2SP/CP | Car door hanger w/ 3 1/4" rollers, track ^E and header | 33" to 44" | 882.80 |
| 1 | 2SP/CP | Car door hanger w/ 3 1/4" rollers, as above | 45" to 57" | 1028.96 |
| 1 | 2SP/CP | Car door hanger w/ 3 1/4" rollers, as above | 58" to 65" | 1108.94 |
| 1 | 2SP/CP | Car door hanger w/ 3 1/4" rollers, as above | 66" to 73" | 1321.26 |
| 1 | 2SP/CP | Car door hanger w/ 3 1/4" rollers, as above | 74" to 83" | 1835.72 |
| 1 | LWZ-2 | Car door clutch w/ zone lock ^A | 33" to 83" | 719.10 |
| 1 | LW2 | Additional car door clutch | 33" to 83" | 571.78 |

Hatch Door Equipment

| Quantity | Type | Description | Opening Size | List |
|----------|--------|--|--------------|--------|
| 1 | 2SP/CP | Hatch door hanger w/ 3 1/4" rollers, top safety retainers ^B , track ^D (ungeared with bumpers), and (2) mechanical interconnecting devices ^C | 33" to 44" | 536.68 |
| 1 | 2SP/CP | Hatch door hanger w/ 3 1/4" rollers, as above | 45" to 57" | 613.88 |
| 1 | 2SP/CP | Hatch door hanger w/ 3 1/4" rollers, as above | 58" to 65" | 684.02 |
| 1 | 2SP/CP | Hatch door hanger w/ 3 1/4" rollers, as above | 66" to 73" | 760.02 |
| 1 | 2SP/CP | Hatch door hanger w/ 3 1/4" rollers, as above | 74" to 83" | 748.32 |
| 2 | 2SP/CP | Spring door closer (\$119.88 each) | | 259.60 |
| 2 | MOH | Interlock - switch, keeper, roller release, linkage and hardware (\$155.52 each) | 33" to 79" | 336.76 |
| 2 | MOH | Interlock - switch, keeper, roller release, linkage and hardware (\$171.72 each) | 80" to 83" | 371.84 |

Optional Door Equipment

| Quantity | Type | Description | List |
|----------|----------|---|--------|
| 1 | DPFS | Formula Systems standard power supply - traditional operators | 648.94 |
| 1 | DPFS | Formula Systems integrated power supply - MOVFR operators only | 570.62 |
| 1 | DPTT | Tri-Tronics standard power supply - traditional operators | 982.18 |
| 1 | DPTT | Tri-Tronics integrated power supply - MOVFR operators only | 906.18 |
| 1 | DPSG | Scanguard standard power supply - traditional operators | 596.32 |
| 1 | DPSG | Scanguard integrated power supply - MOVFR operators only | 521.50 |
| 1 | | Flush type key box - #4 satin stainless steel cover | 74.60 |
| 1 | KMO | Key | 42.80 |
| 1 | Handheld | Handheld parameter w/ 7' cable - for use with MOVFR II operators only | 251.40 |

Issue date: 01/01/21

NORMAL DISCOUNT TO QUALIFIED ELEVATOR CONTRACTORS - PRICES SUBJECT TO CHANGE WITHOUT NOTICE
PRICES BASED ON G.A.L. STANDARD CLEARANCE AND SPACE REQUIREMENTS - F.O.B. BRONX, NEW YORK

CODE REQUIREMENTS:

- (A) ZONE LOCK COMPLIES WITH ASME A17.1 RULE 111.12, CAN/CSA-B44-94 RULE 3.6.5.6
- (B) TOP SAFETY RETAINERS COMPLY WITH ASME A17.1 RULE 110.11h, CAN/CSA-B44-94 RULE 2.11.10.5
- (C) MECHANICAL INTERCONNECTING DEVICES COMPLY WITH ASME A17.1 RULE 110.11g, CAN/CSA-B44-94 RULE 2.12.2.1.7
- (D) SPLIT CAR & HATCH DOOR TRACKS FURNISHED WITH DOOR OPENINGS 74" TO 83"

Car and Hatch Doors Pricing

TWO SPEED / CENTER PARTING / POWER OPERATED CAR DOORS AND
SINGLE SPEED / CENTER PARTING / POWER OPERATED HATCH DOORS
33" TO 83" x 84" OPENINGS (MIN. DOOR PANEL 12 1/2" WIDE)



A VANTAGE Company

Master Door Operator: Drive arm, microswitch and equipped for nudging (add gate switch)

| Quantity | Type | Description | Opening Size | List |
|----------|----------|--|--------------|---------|
| 1 | MODL | Standard duty | 33" to 59" | 2763.20 |
| 1 | MODCTL | Standard duty - car top control | 33" to 59" | 4151.26 |
| 1 | MOVFR II | VVVF - Heavy duty - encoderless closed loop | 33" to 83" | 2923.14 |
| 1 | G | Gate switch assembly - mandatory item | 33" to 83" | 100.74 |
| 1 | G | Shielded gate switch assembly - mandatory item for North Carolina jobs | 33" to 83" | 135.64 |

Car Door Equipment

| Quantity | Type | Description | Opening Size | List |
|----------|--------|--|--------------|---------|
| 1 | 2SP/CP | Car door hanger w/ 3 1/4" rollers, track ^C and header | 33" to 44" | 882.80 |
| 1 | 2SP/CP | Car door hanger w/ 3 1/4" rollers, as above | 45" to 57" | 1028.96 |
| 1 | 2SP/CP | Car door hanger w/ 3 1/4" rollers, as above | 58" to 65" | 1180.94 |
| 1 | 2SP/CP | Car door hanger w/ 3 1/4" rollers, as above | 66" to 73" | 1321.26 |
| 1 | 2SP/CP | Car door hanger w/ 3 1/4" rollers, as above | 74" to 83" | 1835.72 |
| 1 | LWZ-2 | Car door clutch w/ zone lock ^A | 33" to 83" | 719.10 |
| 1 | LW2 | Additional car door clutch | 60" to 83" | 571.78 |
| 1 | | Door link and bracket | 33" to 59" | 66.18 |

Hatch Door Equipment (one required per hatch opening)

| Quantity | Type | Description | Opening Size | List |
|----------|-------|--|--------------|--------|
| 1 | CP | Hatch door hanger w/ 3 1/4" rollers, top safety retainers ^B , cable geared and track ^D | 30" to 35" | 259.58 |
| 1 | CP | Hatch door hanger w/ 3 1/4" rollers, as above | 36" to 44" | 297.00 |
| 1 | CP | Hatch door hanger w/ 3 1/4" rollers, as above | 45" to 50" | 333.24 |
| 1 | CP | Hatch door hanger w/ 3 1/4" rollers, as above | 51" to 59" | 370.60 |
| 1 | CP | Hatch door hanger w/ 3 1/4" rollers, as above but ungeared with bumpers | 60" to 68" | 444.34 |
| 1 | CP | Hatch door hanger w/ 3 1/4" rollers, as above but ungeared with bumpers | 69" to 83" | 517.98 |
| 1 | CP | Spring door closer | 30" to 59" | 88.88 |
| 2 | CP | Spring door closer (\$82.02each) | 60" to 83" | 177.76 |
| 1 | MOCPH | Interlock - switch, keeper, roller release, linkage and hardware | 30" to 59" | 251.40 |
| 2 | MOH | Interlock - switch, keeper, roller release, linkage and hardware (\$155.52 each) | 60" to 79" | 336.76 |
| 2 | MOH | Interlock - switch, keeper, roller release, linkage and hardware (\$171.72 each) | 80" to 83" | 371.84 |

Optional Door Equipment

| Quantity | Type | Description | List |
|----------|----------|---|--------|
| 1 | DPFS | Formula Systems standard power supply - traditional operators | 648.94 |
| 1 | DPFS | Formula Systems integrated power supply - MOVFR operators only | 570.62 |
| 1 | DPTT | Tri-Tronics standard power supply - traditional operators | 982.18 |
| 1 | DPTT | Tri-Tronics integrated power supply - MOVFR operators only | 906.18 |
| 1 | DPSG | Scanguard standard power supply - traditional operators | 596.32 |
| 1 | DPSG | Scanguard integrated power supply - MOVFR operators only | 521.50 |
| 1 | | Flush type key box - #4 satin stainless steel cover | 74.60 |
| 1 | KMO | Key | 42.80 |
| 1 | Handheld | Handheld parameter w/ 7' cable - for use with MOVFR II operators only | 251.40 |

Issue date: 01/01/21

**NORMAL DISCOUNT TO QUALIFIED ELEVATOR CONTRACTORS - PRICES SUBJECT TO CHANGE WITHOUT NOTICE
PRICES BASED ON G.A.L. STANDARD CLEARANCE AND SPACE REQUIREMENTS - F.O.B. BRONX, NEW YORK**

CODE REQUIREMENTS:

- (A) ZONE LOCK COMPLIES WITH ASME A17.1 RULE 111.12, CAN/CSA-B44-94 RULE 3.6.5.6
- (B) TOP SAFETY RETAINERS COMPLY WITH ASME A17.1 RULE 110.11h, CAN/CSA-B44-94 RULE 2.11.10.5
- (C) SPLIT CAR DOOR TRACKS FURNISHED WITH DOOR OPENINGS 60" TO 83"
- (D) SPLIT HATCH DOOR TRACKS FURNISHED WITH DOOR OPENINGS 74" TO 83"